



Tieback secured to a structurally sound anchorage on the building or structure (capable of holding 4 times the hoists rated load capacity).

1,500 lb Maximum Load Capacity with 4 to 1 safety factor
 (6,000 lb Ultimate Load Capacity)

When using a 1,000 lb rated hoist and a 24" outreach:
 $F = 24 \times 1000 / (20.2 - 9.4) = 2,222$ lb working load
 (8,889 lb incl. safety factor)

Working Load (F):		
Outreach (in)	1,000 lb Rated Hoist	1,500 lb Rated Hoist
16.0"	1,481 lb	2,222 lb
20.0"	1,852 lb	2,778 lb
24.0"	2,222 lb	3,333 lb

1	Released for production	BJA	07-21-14
REV	Revision Description	By	Date
DEBUR AND BREAK SHARP EDGES			
Material: Assembly		Weight: 45 LBS	
Treatment: N/A		45 LBS	
Raw material part number:	Dimensions in [] are in mm Tol. ISO 2768-m		<p>The information contained in this drawing is the sole property of Bee Access Products. Any reproduction in part or whole without the written permission of Bee Access Products is strictly prohibited.</p>
Assembly	>	0,5 6 30 120 400	
	<	6 30 120 400	
Scale: 1:16 B/A3		Machined surfaces 12.5 ISO 1302	
CAD generated drawing. Do not manually update. Do not scale drawing.		Unless otherwise stated tolerances in inches	
Approvals By:	Date:	Fractions	Decimals
Drawn: BJA	07-21-14		X ± .060 XX ± .015 XXX ± .005
Approved:	XX-XX-XX		ALL ± .5°
Product Line/Project: Rigging		REV. 1	
Part No. 920152 App		Sheet 1 of 1	